

Versilux® Lining

What is it?

A flat sheet with square edges for butt joints. Sanded smooth and pre-sealed, Versilux lining is a flat surface that is site-painted to create a panelised look.

Where do you use it?

As an internal wall and ceiling lining in laundries, kitchens and high-traffic areas in residential, medium-density and commercial buildings, where a durable, flat panel look is required. It can also be used in exposed beam ceilings and soffits, and is suitable on either timber or light gauge steel framed buildings.

What are the key benefits?

Affordability.

Versilux lining is sanded and pre-sealed, making it easy to paint, and reducing the finishing time and cost.

Design flexibility .

It's easy to achieve a range of looks with Versilux lining using straight PVC jointers, battens or Scyon™ Axent™ trim, as bold or subtle highlights over their smooth, flat surface.

Durability.

The high impact resistance of Versilux lining, compared to plasterboard lining, makes it the smart choice for high-traffic areas that are prone to wear and tear.

Fast installation.

Versilux lining is lightweight and its square edges, together with the wide range of James Hardie™ accessories, make it easy and fast to install by tradespeople, owner-builders and renovators.

Versatility.

It's suitable for use in fire-rated and acoustically rated systems. To add to this, the 6mm thick sheet can also be used as internal bracing.

Security.


Versilux lining is resistant to damage from termites, rot and fire. A 10-year product warranty gives peace of mind.

Length (mm)	Width (mm)	Thickness (mm)	Mass (kg/m ²)
3000	900	6mm	9.4
2400	1200		
2700	1200		
3000	1200		
3600	1200		
2700	1200	9mm	13.7

Accessories


James Hardie™ PVC Eave and Soffit Joints for use with 6mm thick sheets

A black PVC extrusion used to join 6mm thick Versilux® or HardieFlex™ sheets in eave and soffit applications, to give an expressed joint look. Not suitable for external wall cladding applications



James Hardie™ PVC Straight Joints for use with 6mm thick sheets

PVC extrusion used to join sheets



Straight jointer detail

